

# HEAVY PROFESSIONAL WASHER EXTRACTORS SPECIFICATIONS

20 LB and 25 LB CAPACITY



Our extractors provide precise control over cycle settings—water volume, temperature, and spin speed—and come in various capacities and configurations, making them ideal for any firehouse.

## FEATURES

- Soft Mount for easy installation
- User-friendly 4.3" touchscreen to easily navigate through wash cycle options
- Soap Box with 4 independently flushed compartments ideal for detergent applications
- Hot Water and Cold Water Inlet
- Dosing Signals for automated detergent pumps
- NFPA compliant bunker gear wash cycles
- Stainless steel construction- drum, side panels, top, and base
- 15" base for better ergonomics
- Silicon Gasket
- Levelling Feet

## WATER TEMPERATURE CONFIGURATIONS

- Electrically heated drum to maintain 120°F
- Or
- Hot water supplied by stations hot water tank

## DRAINAGE CONFIGURATIONS

- 2" Gravity Drain Valve to Floor Drain or Drain Trough
- Or
- 1" Pump Drain to Wall Drain Pipe.

## DISPENSER OPTIONS

- Standard Soap Box with 4 Independently Flushed Compartments ideal for pre wash and main wash applications
- Additional 6 signals available for automated detergent pumps.

## MORE INFO

CE, WRAS, and ETL approved.



# HEAVY PROFESSIONAL WASHER EXTRACTORS SPECIFICATIONS

20 LB and 25 LB CAPACITY



TECHNICAL DATA	UNIT	RA-PRO20 20-LB.		RA-PRO25 25-LB.	
<b>DRUM</b>					
Load Capacity	lb	20		25	
Volume	cu ft	3		4	
Diameter	in	20.95		20.95	
Depth	in	14.17		16.73	
<b>GENERAL DETAILS</b>					
Water Volume in Pre Soak Phase	gal	6.3		7.45	
Water Volume in Main Wash Phase	gal	3.92		4.63	
Noise level	dB	<70		<70	
<b>DOOR</b>					
Height to Middle of Door	in	36.25		36.25	
Diameter	in	14.69		14.69	
<b>POWER</b>					
Motor	kW	0.75		0.75	
Electric heating power	kW	6		6	
Total Electric Power – Electrically Heated Drum	kW	6.25		6.25	
Total Electric Power – Hot Water Tank Supply	kW	0.75		0.75	
<b>CONNECTIONS</b>		<b>Electric</b>		<b>Water</b>	
110V/50-60Hz/1	Fl Amp	-	10A	-	10A
230V/50-60Hz/3	Fl Amp	20A	-	20A	-
230V/50-60Hz/1	Fl Amp	32A	6A	32A	6A
Water inlet	inch	3/4"		3/4"	
Drain	inch	2" 1" (Pump)	2" 1" (Pump)	2" 1" (Pump)	2" 1" (Pump)
<b>DIMENSIONS/PACKING DIMENSIONS</b>					
Width/width	in	26.77/28		26.77/28	
Depth/depth	in	27.4/33		30.39/33	
Height/height	in	54.72/58.22		54.72/58.22	
Net weight/Gross weight	lb	309/331		309/331	311/352

Specifications subject to change without notice. Please visit [www.ramairgeardryer.com](http://www.ramairgeardryer.com) or contact Ram Air for most current specifications.

# HEAVY PROFESSIONAL WASHER EXTRACTORS SPECIFICATIONS

20 LB and 25 LB CAPACITY



- 1. SOAP DISPENSER
- 2. USB PORT
- 3. DRAIN
- 4. MAIN SWITCH
- 5. ELECTRIC CONNECTION TO LIQUID SOAP PUMPS
- 6. ELECTRICAL CONNECTION (NOT INCLUDED)
- 7. LIQUID SOAP CONNECTION
- 8. COLD WATER INLET
- 9. HOT WATER INLET

